



INDUCTION LOW STOCK POT

- High quality stainless steel #304, hairline finished body construction with solid top 1.5mm thickness.
- Powerful performance, high energy efficiency & quiet operation
- No open flame, no gas emission, reduces environmental pollution
- Electromagnetic heating up, thermal efficiency is over 90%.
- Microcomputer temperature control system
- User friendly & easy for cleaning and no intensive maintenance required.
- High-grade ceramic concave glass for heavy duty performance and durability.
- Patented copper coil for powerful and uniform heat for better cooking.
- Empty pan detection auto shut-off.
- Over/under voltage/current protection
- Over heat and dry burning protection
- Soft start technology, automatic alarm device for safety operation.
- Waterproof display, anti-oil, water and, insect erosion design









- Ultra-long life magnetic sensor switch and PCB board for precise performance.
- IPX4 protection level with multiple protection

CONSTRUCTION & FEATURES

		
Model	TIA-S75SP1	TIA-S75SP2
Dimension (mm)	650 x 750 x 1200H	1200 x 750 x 1200H
Power (kW)	1 x 15 kW	2 x 15 kW
Glass size (mm)	Ø400	Ø400
Voltage	380V/50Hz,3P	380V/50Hz,3P

SPECIFICATIONS

Induction Low Stockpot



TECHNICAL DRAWINGS



m: +65-9038-0875
e: sales@trutech.sg
w: www.trutech.sg

TRUTECH PTE. LTD
470 North Bridge Road, #5-12 Bugis Cube,
Singapore (188735)