

## INDUCTION GRIDDLE (FRY TOP)

- High quality stainless steel #304, hairline finish body construction with special steel solid top up to 20mm thickness.
- Powerful performance, high energy efficiency & quiet operation
- Intelligent temp. control minimize smoke and avoid food burning.
- User and environmental friendly & easy for cleaning, no intensive maintenance required.
- Patented coper coil for powerful and uniform heat for better cooking.
- Over/under voltage/current protection
- Over heat and dry burning protection
- Soft start technology, automatic alarm device for safety operation.
- Waterproof display, anti-oil, water and, insect erosion design
- Ultra-long life magnetic sensor switch and PCB board for precise performance.
- IPX4 protection level with multiple protection
- Choice of smooth or with part-ribbed top



CONSTRUCTION & FEATURES

SERIES 750MM			
Model	TIW-S75G400	TIW-S75G800	TIW-S75G1200
Dimension (mm)	400 x 750 x 850H	800 x 750 x 850H	1200 x 750 x 850H
Power (kW)	6kW	8kW	2*6kW
Voltage	380V/50Hz,3P	380V/50Hz,3P	380V/50Hz,3P

SERIES 900MM			
Model	TIW-S90G400	TIW-S90G800	TIW-S90G1200
Dimension (mm)	400 x 900 x 850H	800 x 900 x 850H	1200 x 900 x 850H
Power (kW)	6kW	8kW	2*6kW
Voltage	380V/50Hz,3P	380V/50Hz,3P	380V/50Hz,3P

SPECIFICATIONS



