

SPECIFICATIONS

INDUCTION GUANGDONG WOK

- High quality stainless steel #304, hairline finish body construction with solid top 1.5mm thickness.
- Powerful performance, high energy efficiency & quiet operation
- No open flame, no gas emission, reduces environmental pollution
- Electromagnetic heating up, thermal efficiency is over 90%.
- Microcomputer temperature control system
- User friendly & easy for cleaning and no intensive maintenance required.
- High-grade ceramic concave glass for heavy duty performance and durability.
- Patented coper coil for powerful and uniform heat for better cooking.
- Empty pan detection auto shut-off.
- Over/under voltage/current protection
- Over heat and dry burning protection
- Soft start technology, automatic alarm device for safety operation.



- Waterproof display, anti-oil, water and, insect erosion design
- Ultra-long life magnetic sensor switch and PCB board for precise performance.
- IPX4 protection level with multiple protection

Optional: Custom as Design Request

SERIES 1000MM	Eower control	E Commence and the Comm
Model	TIA-S100GW1	TIA-S100GW2
Dimension (mm)	950 x 1000 x 1200H	1800 x 1000 x 1200H
Power (kW)	1 x 12 kW (15kW optional)	2 x 12 kW (15kW optional)
Wok size (mm)	Ø600	Ø600
Voltage	380V/50Hz,3P	380V/50Hz,3P





m: +65-9038-0875 e: sales@trutec.sg w: www.trutec.sg


Induction Guangdong Wok




















m: +65-9038-0875 e: <u>sales@trutec.sg</u> w: <u>www.trutec.sg</u>