

- High quality stainless steel #304, hairline finished body construction with solid top 1.5mm thickness.
- Powerful performance, high energy efficiency & quiet operation
- No open flame, no gas emission, reduces environmental pollution
- Electromagnetic heating up, thermal efficiency is over 90%.
- Microcomputer temperature control system, individually deck or section operated.
- User friendly & easy for cleaning and no intensive maintenance required.
- Patented coper coil for powerful and uniform heat for better cooking.
- Over/under voltage/current protection
- Over heat and dry burning protection
- Soft start technology, automatic alarm device for safety operation.
- Waterproof display, anti-oil, water and, insect erosion design



- Ultra-long life magnetic sensor switch and PCB board for precise performance.
- IPX4 protection level with multiple protection

DIMSUM STEAMER SERIES 900MM			
Model	TIA-S90D3	TIA-S90UP1	TIA-S90UP2
Dimension (mm)	900 x 900 x 1850H	650 x 900 x 1850H	1150 x 900 x 1850H
Power (kW)	1 x 25 kW (30kW optional)	1 x 15 kW (20kW optional)	2 x 15 kW (20kW optional)
Voltage	380V/50Hz,3P	380V/50Hz,3P	380V/50Hz,3P





CONSTRUCTION & FEATURES

Induction Deck Steamer





















